

# Questionnaire for Joints Straight Through (Standard)

## Cable Data

1. Cable Manufacturer: .....
2. Cable Type:  Single Core  Three Core

## Cable 1

### System Voltage (Voltage Class)

- <1000V
- 3.6/6kV
- 6.35/11kV
- 12.7/22kV
- 19/33kV

Cable Material  Al  Cu

Special Requirements:.....  
.....

Conductor Size:.....mm<sup>2</sup>

(16 - 25 - 35 - 50 - 70 - 95 - 120 - 150 - 185 - 240 - 300 - 400 - 500 - 630 - 800 - 1000 mm<sup>2</sup>)

Core Insulation Type  XLPE  EPR  Paper

Diameter:.....mm

Armour Type  No  SWA /AWA (Steel Wired Armour)

Outer Sheath Diameter:..... mm

## Cable 2

### System Voltage (Voltage Class)

- <1000V
- 3.6/6kV
- 6.35/11kV
- 12.7/22kV
- 19/33kV

Cable Material  Al  Cu

Special Requirements:.....  
.....

Conductor Size:.....mm<sup>2</sup>

(16 - 25 - 35 - 50 - 70 - 95 - 120 - 150 - 185 - 240 - 300 - 400 - 500 - 630 - 800 - 1000 mm<sup>2</sup>)

Core Insulation Type  XLPE  EPR  Paper

Diameter:..... mm

Armour Type  No  SWA /AWA (Steel Wired Armour)

Outer Sheath Diameter: .....mm

CUSTOMER:.....

PROJECT NAME:.....

CABLE SPECIFICATION SUPPLIED  Yes  No